



**HERON**  
INSTRUMENTS INC.  
Groundwater Monitoring

## dipper-T Water Level Meter

Now with **drawDown** Mode

Length options: 50ft/15m to 2000ft/600m

Warranty: 5 years, probe 1 year

The **dipper-T** water level meter is a topline, top quality instrument used for measuring **static** and **falling** head levels in wells and boreholes. With a touch of a button the unit changes from **static** to **drawDown** mode; a dual function unit at an affordable price.

The **dipper-T** in **static** mode is used for measuring the depth of water in wells, boreholes and standpipes. The **dipper-T** in **drawDown** mode may be used for measuring **falling** water levels during purging, well development and for low flow sampling; helping to protect your pumps from damage caused by dry running.



### Features included with the dipper-T:

- **Electronic Module (IP65)** – mode selectable for **static** and **drawDown** levels, removable for easy cleaning and servicing
- **Probe (IP68)** – fully pressure/depth rated, **field replaceable** for optional casing or bottom detector probes
- **Steel Tape** – high tensile steel, jacketed with polyethylene, high break strength, stretch resistant and lifelong legibility
- **Padded Carry Case** – to protect your **precision** water level meter from the elements
- **Tape Guide And Hanger** – to support the meter at the well head and to **protect** the tape from sharp edges on the well casing
- **Vinyl Holding Grip** – molded to the frame, **ergonomic** easy grip
- **Winding Handle** – custom made for **easy** rewinding with gloved hands

### Available options:

- Narrow 3/8 inch probe (not removable)
- Well depth indicator probe
- Well casing indicator probe
- Potable Water only model



**FieldTech Solutions**

Tel - +61 3 9676 9664








37 Wirraway Drive, Port Melbourne, VIC.3207

Email - [sales@fieldtechsoln.com](mailto:sales@fieldtechsoln.com)




## WATER LEVEL METERS

### SELECTION GUIDE:

		Tape (see below for details)	drawDown Electronics	Fully Submersible Probe	Field Replaceable Probe	3/8" Narrow Probe Available (not detachable)	Tape Guide and Hanger	Audio/Visual Sensor	9 Volt Battery	Temperature	Padded Carry Case	Cloth Carry Case	5 Year Product and 1 Year Probe Warranty *	3 Year Product and 1 Year Probe Warranty *	Tape Lengths **
<b>WATER LEVEL METERS</b>	 <b>dipper-T</b>	A	•	•	•	•	•	•	•		•		•		50ft/15m to 1000ft/300m
	 <b>Water Tape</b>	C		•		•	•	•	•			•		•	100ft/30m to 1000ft/300m
	 <b>Little Dipper</b>	A	•	•	•	•	•	•	•		•			•	75ft / 22m
	 <b>skinnyDipper</b>	C					•	•	•			•		•	100ft/30m to 500ft/150m
	 <b>mega reel</b>	A C	•	•	•	•		•	•		•			•	1500ft/400m and up
<b>CONDUCTIVITY/ TEMPERATURE WATER LEVEL METERS</b>	 <b>Conductivity Plus</b>	A		•	•		•	•	•	•	•			•	100ft/30m to 1000ft/300m
	 <b>Temperature Meter</b>	B		•	•		•	•	•	•	•			•	100ft/30m to 500ft/150m

\* Warranties cover manufactured defect.

\*\* Longer tape lengths and Power Reel are available.

 <p>Fully pressure/depth rated, IP68 field replaceable probes</p>	 <p>Tape Guide and Hanger</p>	<div data-bbox="925 1164 1053 1388">  <p><b>A</b> = High tensile steel tape, jacketed with polyethylene, high break strength, stretch resistant and lifelong legibility</p> </div> <div data-bbox="893 1433 1340 1534"> <p><b>B</b> = High tensile steel tape, jacketed with heat and hydrocarbon resistant Kynar, high break strength, stretch resistant and lifelong legibility</p> </div> <div data-bbox="925 1568 1053 1792">  <p><b>C</b> = White polyethylene tape, reinforced with stretch resistant Kevlar</p> </div>	
 <p>Padded Carry Case</p>	 <p>Rewinding Handle and Vinyl Holding Grip</p>		



**FieldTech Solutions**

Tel - +61 3 9676 9664

37 Wirraway Drive, Port Melbourne, VIC.3207

Email - sales@fieldtechsoln.com