Mi106 Portable pH/ORP/Temp Meter

Extended Range pH/ORP/Temperature Meter

The Mi106 multi parameter portable meter is ideal for field measurements.

The included combined pH/ORP electrode has a built-in temperature sensor and amplifier to prevent electrical

The large display shows readings in an extended range from -2.00 to 16.00 pH or ±2000 mV and simultaneously shows temperature from -5.0 to 105.0°C or 23 to 221°F.

The Mi106 has a stability indicator and hold feature that freezes the display for easy and accurate recording. The large display also has graphic symbols to guide you through all operations.

When switched ON it performs a self-check and displays the percentage of the remaining battery level to assure proper working condition.

Calibration is performed automatically at 1 or 2 points using standard or NIST buffers.



MA9004

MA9007

MA9015

MA9016

Accessories

MA923D/1 Combination amplified pH/ORP/Temp probe with DIN connector and 1 m cable

M10000B Electrode rinse solution, 20 mL

sachet (25 pcs)

M10004B pH 4.01 buffer solution 20 mL

sachet (25 pcs)

M10007B pH 7.01 buffer solution 20 mL

sachet (25 pcs)









Ordering Information

Hard Carrying Case

field measurements.

Each meter is supplied in a hard carrying case ideal for

Mi106 is supplied complete with MA923D/1 pH/ORP/Temp amplified probe with 1 meter cable, 20 mL pH 4.01 and 7.01 sachet of calibration solution, 2x20 mL sachet of electrode cleaning solutions, 9V battery, instructions, all in a rugged carrying case.



Specifications		Mi106
Range (*)	pН	-2.00 to 16.00 pH
	mV	-2000 to +2000 mV
	Temp	-5.0 to 105.0°C / 23.0 to 221.0°F
Resolution	рН	0.01 pH
	_ mV	1 mV
	Temp	0.1°C / 0.1°F
Accuracy (@25°C)	pН	±0.02 pH
	_ mV	±2 mV
	Temp	±0.5°C up to 60°C; ±1°C outside / ±1°F up to 140°F; ±2°F outside
Typical EMC Deviation	pН	±0.02 pH
	_ mV	±2 mV
·	Temp	±0.2°C / ±0.4°F
Temperature Compensation		automatic, from -5 to 80°C / 23 to 176°F
pH Calibration		automatic, 1 or 2-point
ORP Calibration		factory calibrated
Probe		MA923D/1, amplified pH/ORP/temperature probe (included)
Environment		0 to 50°C / 32 to 122°F; max RH 95%
Battery Type		1 x 9V alkaline (included)
Battery Life		approx. 500 hours of use
Auto-off		after 8 minutes of non-use
Dimensions		200 × 85 × 50 mm
Weight		260 g (with battery)

(*) The temperature range is limited to 80°C (176°F) if using the MA923D/1 probe.

M10010B pH 10.01 buffer solution 20 mL

sachet (25 pcs)





pH 4.01 buffer solution, 230 mL bottle

pH 7.01 buffer solution, 230 mL bottle

Electrode storage solution, 230 mL

Electrode cleaning solution, 230 mL





FieldTech Solutions

Tel - +61 3 9676 9664

37 Wirraway Drive, Port Melbourne, VIC.3207 Email - sales@fieldtechsoln.com