

# CETCO® COATED TABLETS

## BENTONITE TABLETS – TIME RELEASED FOR SEALING AND PLUGGING



### DESCRIPTION

CETCO COATED TABLETS are coated using an aqueous carrier to apply the coating. The coating allows the tablets to reach a discrete depth within the waterwell, piezometer, monitoring well, or annular space. These untreated organic tablets are compressed into 1/4" (0.64 cm) and 3/8" (0.95 cm) sizes. CETCO COATED TABLETS are certified to NSF/ANSI Standard 60, Drinking Water Treatment Chemicals - Health Effects.

### RECOMMENDED USE

CETCO COATED TABLETS are designed to fall through standing water columns of up to 500 vertical feet without bridging. CETCO COATED TABLETS form a chemically resilient, low-permeability, flexible seal.

- Isolate screen intervals, subsurface instrumentation, and sampling zones
- Plug abandoned boreholes and cavities
- Provide a protective barrier between gravel pack and high solids grout
- Seal or grout plastic or steel casing

Build a stable, permanent below-grade seal in:

- Caisson holes
- Mineral exploration holes
- Monitoring/observation wells
- Piezometer/water sampling wells
- Soil/geotechnical sampling holes
- Waterwells

### PACKAGING

~50 lb (22.7 kg) pails, 36 per pallet. All pallets are plastic-wrapped.

### MIXING AND APPLICATION

#### 1/4" (0.64 cm) CETCO COATED TABLETS REQUIRED FOR SEALING AND PLUGGING APPLICATIONS

Hole Diameter (in)	Hole Volume ft³/ft	Lbs/linear ft	Hole Diameter (cm)	Hole Volume m³/m	Kg/linear meter
2	0.02	1.61	5	0.001	0.72
4	0.09	7.26	10	0.003	3.27
6	0.20	16.14	15.2	0.006	7.26
8	0.35	28.25	20.3	0.011	12.7
10	0.55	44.40	25.4	0.017	20.0
12	0.79	63.77	30.5	0.024	28.7
16	1.40	113.01	40.6	0.040	50.9
36	7.07	570.69	91.4	0.212	256.8

#### 3/8" (0.95 cm) CETCO COATED TABLETS REQUIRED FOR SEALING AND PLUGGING APPLICATIONS

Hole Diameter (in)	Hole Volume ft³/ft	Lbs/linear ft	Hole Diameter (cm)	Hole Volume m³/m	Kg/linear meter
2	0.02	1.59	5	0.001	0.72
4	0.09	7.15	10	0.003	3.22
6	0.20	15.88	15.2	0.006	7.15
8	0.35	27.80	20.3	0.011	12.5
10	0.55	43.68	25.4	0.017	19.7
12	0.79	62.74	30.5	0.024	28.2
16	1.40	111.19	40.6	0.040	50.0
36	7.07	561.50	91.4	0.212	252.7

Fieldtech Solutions Pty Ltd  
Tel – 03 9676 9664; sales@fieldtechsoln.com

North America: 847.851.1800 | 800.527.9948 | www.CETCO.com

UPDATED: SEPTEMBER 2019

© 2019 CETCO. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit [www.CETCO.com](http://www.CETCO.com). CETCO accepts no responsibility for the results obtained through application of this product. All products are sold on the understanding that the user is solely responsible for determining their suitability for the intended use and for proper use and disposal of the product. CETCO MAKES NO WARRANTY OF MERCHANTABILITY OR SUITABILITY FOR ANY PARTICULAR PURPOSE IN CONNECTION WITH ANY SALE OF THE PRODUCTS DESCRIBED HEREIN. CETCO reserves the right to update information without notice.

FORM: TDS\_CETCO\_COATED\_TABLETS\_AM\_EN\_201909



**CETCO®**