

# CETCO® SET30

## HIGH STRENGTH GYPSUM BASED CEMENT

### DESCRIPTION

CETCO SET30 is a high strength gypsum based cement designed to set hard in a given time.

### RECOMMENDED USE

CETCO SET30 can be used to cement surface casing or pipe in air drilling applications.

### CHARACTERISTICS

- ▶ Controlled setting time.
- ▶ Plugging lost circulation zones
- ▶ Provides a shear thinning/pumpable slurry
- ▶ Cementing unstable ground formations
- ▶ Reduced rig time waiting on cement to set
- ▶ Cementing casing/pipe

### MIXING AND APPLICATIONS

CETCO SET30 is mixed at a ration of 8 kg of CETCO SET30 to every 5 litres of water.

Note: Temperature and water quality will effect setting time, care must be taking to ensure setting time is carefully considered.

### TYPICAL PROPERTIES

Appearance	off-white powder
Bulk Density	2.50

### PACKAGING

20 kg pail, 32 per pallet. All pallets are plastic-wrapped.

Fieldtech Solutions Pty Ltd.  
Tel – 03 9676 9664; [sales@fieldtechsoln.com](mailto:sales@fieldtechsoln.com)

UPDATED: OCTOBER 2013

© 2013 CETCO. IMPORTANT: The information contained herein supersedes all previous printed versions, and is believed to be accurate and reliable. For the most up-to-date information, please visit [www.CETCO.com](http://www.CETCO.com). CETCO accepts no responsibility for the results obtained through application of this product. CETCO reserves the right to update information without notice.



[www.CETCO.com](http://www.CETCO.com)  
50 Crowle St. East, North Geelong, VIC 3215  
+61.3.52782555 | 800.527.9948